

# Self-Leveling Combination Cross-Line/Point Laser

CATALOG (SKU) NUMBER: MK-SK103PZ

Provides all possible reference lines required in leveling, aligning, plumbing, and squaring applications for maximum versatility. Line visibility range up to 50' and point visibility range up to 100' depending on ambient light in working environment. Accuracy - horizontal/vertical lines ( $\pm 1/8"$  @ 30'); points ( $\pm 1/8"$  @ 30'). Fast self-leveling time; stability is achieved in 3 seconds for increased productivity. Self-leveling is correctable up to 4° of slope allowing operation on uneven surfaces. Bright 635 nm class II laser for best-in-class visibility in moderate ambient light environment. Laser line fan length spans well past 90° point position to provide 180° horizontal line and 120° vertical line for full reference line coverage in demanding applications. Integrated pendulum lock enables slope incline applications for increased versatility. Pulse mode allows operation with laser receiver with detection achieved up to 200'. Pulse mode conserves and extends battery life for increased operation time in low light environments. Delivers up to 35 hours of continuous run time operation. Five dedicated mode functions conserve power by allowing battery power usage only when needed to operate the necessary functions. Recessed laser windows are highly protected from fracture damage in slot positions for increased durability. Full oversized rubber over-mold for increased protection. Pendulum lock offers added protection of laser diode during transport and storage. Dust and water resistance with IP 54 rating for increased durability. Simplified two button user interface for ease of operation. Integrated bracket allows for attachment to a tripod with a 1/4" & 5/8" thread or to metal and wood objects.