

# Alloy Master Link Grade 100 (Peerless)

CATALOG (SKU) NUMBER: PEER-8851

- For use with grade 80 or 100 chain slings, wire rope, and synthetic assemblies.
- Design factor is 4:1.
- Meet or exceed all requirements of ASME B30.26.
- Proof tested in accordance with ASTM A952.
- Available in Chinese import or U.S.A. domestic upon request.



G-100 Masterlink



oblong master link

## Product Specifications

ALLOY MASTER LINKS (PEERLESS) GRADE 100								
PART NUMBER	SIZE (IN)	SIZE (MM)	WORKING LOAD LIMIT (LBS)	DIMENSIONS (IN)			WEIGHT EA (LBS)	COUNTY OF ORIGIN
				A	B	C		
PEER-8851000	1/2	13	7,000	0.512	2.362	4.331	0.7	GERMANY
PEER-8851100	5/8	16	11,400	0.63	2.362	4.331	1.2	GERMANY
PEER-8851200	3/4	18	12,300	0.709	2.953	5.315	1.8	GERMANY
PEER-8851300	7/8	23	17,200	0.866	3.543	6.299	3.3	GERMANY
PEER-8851400	1	27	29,900	1.024	3.937	7.087	5.1	GERMANY
PEER-8851500	1-1/4	33	35,200	1.26	4.331	7.874	8.6	GERMANY
PEER-8851600	1-1/2	38	68,000	1.496	5.906	10.827	16.5	GERMANY
PEER-8851700	1-3/4	45	84,900	1.772	7.087	13.386	28.2	GERMANY
PEER-8851800	2	50	102,600	1.969	7.48	13.78	36.4	GERMANY
PEER-8851900	2-1/4	60	143,100	2.362	7.874	15.748	59.5	GERMANY