

# Alloy Swivel Hoist Hook With Latch

CATALOG (SKU) NUMBER: CA-SH/CT-395

- Heat Treated Alloy Steel.
- Design Factor is 5:1.
- All Hooks Drilled For Latch.
- Swivel hooks are not designed to swivel under load.



Swivel Hook Alloy



swivel hoist hookDM

## Product Specifications

ALLOY SWIVEL HOIST HOOK (WITH LATCH)	SIZE/ WORKING LOAD LIMIT (TONS)	IMPORT PART NUMBER	DOMESTIC PART NUMBER	WEIGHT (LBS)	DIMENSIONS (IN)											REPLACEMENT LATCH PART NUMBER (IMPORT)	REPLACEMENT LATCH PART NUMBER (DOMESTIC)		
					A	B	C	D	E	F	G	H	I	J	K			L	
1	CA-SH13952215	CT-2215		.90	2.0000	0.0000	0.2500	0.9375	0.0313	0.8750	0.7813	0.9063	0.5625	0.6250	0.4625	0.3750	I50330	CT-T7502101	
1.5	-	CT-3952315		1.1	2.5000	0.2500	0.5000	0.2500	0.0313	0.8750	0.8438	0.9688	0.6250	0.6875	0.4375	0.5000	-	CT-T7502101	
2	CA-SH23952415	CT-2415		1.6	2.5000	0.2500	0.5000	0.5625	0.1250	0.0313	0.0313	0.1250	0.6875	0.3125	0.8125	0.5000	I50340	CT-7506495	
3	CA-SH33952515	CT-2515		2.7	3.0000	0.6250	0.7500	0.0000	0.2500	0.1250	0.1563	0.3125	0.8125	0.1875	0.64375	0.6250	I50345	CT-7506495	
4.5	CA-SH53952715	CT-2715		4.5	3.5000	0.7500	0.0000	0.9375	0.5313	0.9375	0.4375	0.6250	0.0625	0.4375	0.0000	0.7500	I50350	CT-7506695	
7	CA-SH73952915	CT-2915		10	4.5000	0.2500	0.5000	0.4688	0.9688	0.6563	0.8125	0.1250	0.3750	0.3750	0.6250	0.0000	I50352	CT-7506895	
11	-	CT-3953115		18.25	5.6250	0.8438	0.1250	0.3438	0.1250	0.0000	0.2500	0.2500	0.6250	0.5000	0.0000	0.5625	0.2500	-	CT-7507095
15	-	CT-3953215		20	5.6250	0.7500	0.1250	0.8125	0.5625	0.1250	0.5625	0.9375	0.8125	0.0313	0.2500	0.2500	-	CT-7507295	