Compact Swaged 6X25 EIPS Grade IWRC Logging Wire Rope

CATALOG (SKU) NUMBER: 6X25

- Compact swaged 6X25 wire rope is typically used for logging rope. It offers excellent crushing resistance and excellent abrasion resistance.
- Rotary swaged and hammered agian to produce a compact cross section with minimal valleys between strands than a standard 6x19 class or even a 6X26 swaged wire rope. This design helps reduce wear to sheaves and prevents crushing of the wire rope when spooling. Highest strength rope available in a 6X19 classification.
- Manufactured in accordance with RR-W-410 standards, preformed, right regular lay. Galvanized wire rope is drawn galvanized.
- Available in import or domestic.
- Mill test certifications available upon request.
- Nominal breaking strengths slightly vary by manufacturer.

PACIFIC Industrial Supply

Product Specifications

LOGGING WIRE ROPE 6X25 COMPACT SWAGED EIPS GRADE IWRC		
SIZE (IN)	APROXIMATE WEIGHT PER FOOT (LBS)	NOMINAL BREAKING STRENGTH (LBS)
1/2	0.630	37,120
9/16	0.790	46,900
5/8	0.970	57,480
3/4	1.390	79,800
7/8	1.870	103,780
1	2.360	135,700
1-1/8	2.890	169,620
1-1/4	3.430	203,560
1-3/8	4.210	238,940