

# Compact Swaged 6X25 EIPS Grade IWRC Logging Wire Rope

CATALOG (SKU) NUMBER: 6X25

- Compact swaged 6X25 wire rope is typically used for logging rope. It offers excellent crushing resistance and excellent abrasion resistance.
- Rotary swaged and hammered again to produce a compact cross section with minimal valleys between strands than a standard 6x19 class or even a 6X26 swaged wire rope. This design helps reduce wear to sheaves and prevents crushing of the wire rope when spooling. Highest strength rope available in a 6X19 classification.
- Manufactured in accordance with RR-W-410 standards, preformed, right regular lay. Galvanized wire rope is drawn galvanized.
- Available in import or domestic.
- Mill test certifications available upon request.
- Nominal breaking strengths slightly vary by manufacturer.

## Product Specifications

<b>LOGGING WIRE ROPE 6X25 COMPACT SWAGED EIPS GRADE IWRC</b>		
SIZE (IN)	APROXIMATE WEIGHT PER FOOT (LBS)	NOMINAL BREAKING STRENGTH (LBS)
1/2	0.630	37,120
9/16	0.790	46,900
5/8	0.970	57,480
3/4	1.390	79,800
7/8	1.870	103,780
1	2.360	135,700
1-1/8	2.890	169,620
1-1/4	3.430	203,560
1-3/8	4.210	238,940