

# Grade 100 Alloy Lifting Chain (Imported)

CATALOG (SKU) NUMBER: RC-040

- Made from heat treated alloy steel.
- Designed for use for overhead lifting and where extreme weight rating is desired.
- Meets all federal specifications for overhead lifting chain.
- 25% stonger than grade 80 chain with lighter weight per foot.
- Standard finish is powder-coated high visibility green paint.
- Proof tested.
- Design factor is 4:1.



G-100 (Import)

## Product Specifications

| LIFTING CHAIN GRADE<br>100 CAM-ALLOY<br>(IMPORTED) |                |                       |                             |                      |                    |        |        |
|--|----------------|-----------------------|-----------------------------|----------------------|--------------------|--------|--------|
| SIZE (IN)  | PART<br>NUMBER | WORKING<br>LOAD LIMIT | WEIGHT<br>PER FOOT<br>(LBS) | LINKS<br>PER<br>FOOT | DIMENSIONS<br>(IN) |        |        |
|  |                |                       |                             |                      | A                  | B      | C      |
| 1/4  | RC-0405212     | 4,300                 | 0.74                        | 14.25                | 0.290              | 0.8320 | 0.3825 |
| 5/16   | RC-0405312     | 5,700                 | 1.04                        | 12.50                | 0.330              | 0.9530 | 0.4525 |
| 3/8  | RC-0405412     | 8,800                 | 1.48                        | 10.00                | 0.400              | 1.1670 | 0.5565 |
| 1/2  | RC-0405512     | 15,000                | 2.50                        | 7.750                | 0.520              | 1.5350 | 0.7235 |