Swaged 6X26 EIPS Grade IWRC Logging Wire Rope

CATALOG (SKU) NUMBER: 6X26-SWA

- Swaged wire rope is typically used for logging rope. It offers excellent crushing resistance and excellent abrasion resistance.
- Rotary swaged to produce a compact cross section with smaller valleys between strands than a standard 6x19 class wire rope. This design helps reduce wear to sheaves and prevents crushing of the wire rope when spooling.
- Manufactured in accordance with RR-W-410 standards, preformed, right regular lay. Galvanized wire rope is drawn galvanized.
- Available in import or domestic.
- Mill test certifications available upon request.
- Nominal breaking strengths slightly vary by manufacturer.



150529_0284PacificIndustrial

PACIFIC Industrial Supply

Product Specifications

LOGGING WIRE ROPE 6X26 SWAGED EIPS GRADE IWRC		
SIZE (IN)	APROXIMATE WEIGHT PER FOOT (LBS)	NOMINAL BREAKING STRENGTH (LBS)
3/8	0.310	18,200
7/16	0.420	24,400
1/2	0.550	32,000
9/16	0.710	40,400
5/8	0.960	49,400
3/4	1.250	70,600
7/8	1.700	95,600
1	2.220	124,000
1-1/8	2.660	158,600
1-1/4	3.470	195,000
1-3/8	4.200	234,000